



## NRT Series for Reactive Gas Service

### Product Information

The NRT series of Krytox™ oils and greases deliver non-reactive, nonflammable, long-lasting performance, even under the demanding temperatures and pressures of reactive gas service. Krytox™ NRT lubricants are compatible with oxygen and other reactive chemicals, and are extremely resistant to water washout. Krytox™ NRT lubricants are also compatible with polymers used in seals, O-rings, and valves.

The superior film-forming capability of Krytox™ lubricants provide a thick oil layer that reduces friction and wear, extending equipment life in severe duty applications. The non-oxidizing nature of the oils makes the greases last longer. The oils don't gum up as they age; so, they won't harden the greases and cause catastrophic failure.

Krytox™ oils and greases are perfluoropolyether (PFPE) lubricants—also called perfluoroalkylether (PFAE) or perfluoropolyalkylether (PFPAE). Many of the NRT series of Krytox™ greases are thickened with a unique polytetrafluoroethylene (PTFE) with the formula  $(CF_2-CF_2)_n$ . This special high efficiency thickener has a melting point of 325 °C (617 °F), low molecular weight, and submicron (0.2 µm) particle size.

**Krytox™ NRT 8904** and **NRT 8906** provide excellent lubrication options for valves, regulators, seals, and pump and motor bearings at a wide range of operating conditions.

**Krytox™ NRT 8906A** provides rust protection at ambient temperatures, corrosion protection at high temperatures, and antiwear protection. This white grease, containing a patented soluble anti-corrosion additive, is designed for bearing applications where anti-corrosion protection is required.

**Krytox™ NRT 8908** grease is a special high-pressure oxygen paste with excellent lubrication over a broad temperature range. This product has been formulated with special oils and thickeners for use in the high-pressure oxygen industry. Krytox™ NRT 8908 has been tested by BAM with typical oxygen ratings of 260 bar at 60 °C (140 °F). This material is not suitable for liquid oxygen service applications.

**Krytox™ NRT 8950** is an extreme high-temperature grease with low oil evaporation. The special non-melting high temperature thickener in Krytox™ NRT 8950 also provides extreme pressure properties and works as a solid lubricant if the base oil is depleted. The base oil provides good viscosity and lower evaporation at high temperatures. The grease is slightly tacky and will provide extra bonding to the surface. Krytox™ NRT 8950 received a rating of 180 bar at 60 °C (140 °F) in the BAM oxygen reactivity test.

**Krytox™ NRT PLSS** is recommended for use in applications requiring an H-1 rated lubricant.

**Krytox™ NRT 8805** is a clear, colorless oil for use in vacuum pumps and oxygen compressors. It has been precisely distilled to provide low vapor pressures and superior performance when compared to conventional vacuum pump oils, which may cause safety, waste disposal, and maintenance problems. Krytox™ NRT 8805 also contains a patented soluble additive to offer anti-rust protection and improved performance properties.

### Product Properties of Krytox™ NRT Series

Typical Properties	NRT 8904	NRT 8906	NRT 8906 A	NRT 8908	NRT 8950	NRT PLSS	NRT 8805
Description	White, creamy grease	White, creamy grease	White, creamy grease	Light gray, creamy paste	White, creamy grease	White, creamy grease	Clear, colorless oil
NLGI Grade	2	2	2	2	1.5	2	—
Thickener	PTFE	PTFE	PTFE	Inorganic	Non-melting	PTFE	—
Estimated Useful Temperature Range, °C (°F)	-51-179 (-60-354)	-36-260 (-33-500)	-36-200 (-33-392)	-40-180 (-40-356)	-15-325 (5-617)	-36-260 (-33-500)	-40-160 (-40-320)
Oil Viscosity, kinematic cSt, ASTM D445, °C (°F)							
40 (104)	60	240	240	49	500	240	81
100 (212)	9	25	25	7.2	47	25	11
204 (399)		4	4			3.9	
Oil Density, g/mL	1.93	1.95	1.95	2.0	1.95	1.95	1.9
Max. Oil Volatility, % in 22 hr, ASTM D972, °C (°F)							
66 (151)	1						
121 (250)	3	1	1	2		1	1
204 (399)		<5	<6		<1	<5	
260 (500)					2.1		

The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Because conditions of product use are outside our control, Chemours makes no warranties, express or implied, and assumes no liability in connection with any use of this information. As with any material, evaluation of any compound under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

**CAUTION:** Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative. For medical emergencies, spills, or other critical situations, call (866) 595-1473 within the United States. For those outside of the United States, call (302) 773-2000.

NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF CHEMOURS.

For product information, industry applications, technical assistance, or global distributor contacts, visit [krytox.com](http://krytox.com) or within the U.S. and Canada, call 1-844-773-CHEM/2436 or outside of the U.S., call 1-302-773-1000.